

EVE F-160ZQ

EN RÉSUMÉ

- Full-color Fresnel designed for mobile and installation applications
- Integrated zoom optics ensure subject remains in the spotlight from a wide range of distances
- Pre-set color temperature ranges eliminate the need for manual color blending
- Flicker-free operation suitable for on-camera use
- D-Fi USB compatibility for wireless master/slave or DMX control
- powerCON®-compatible power input/output connections for power linking

CARACTÉRISTIQUES TECHNIQUES

- DMX Channels : 3, 4 or 11
- DMX Connectors : 3- and 5-pin XLR
- Light Source : 1 LED (quad-color RGBW) 160 W, (7.3 A), 50,000 hours life expectancy
- Beam Angle : 16° - 61°
- Field Angle : 29° - 90°
- Power Linking : 9 units @ 120 V; 16 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Zoom Angle : 24° to 37°
- Weight : 12.2 lb. (5.5 kg)
- Size : 18.4 x 9.8 x 16.9 in (467 x 248 x 429 mm)
- Approvals : CE, RoHS, MET
- Accessory Holder Size : 6.25 in
- Color Temperature Range : 2800 K – 8000 K
- Strobe Rate : 1 to 30 Hz
- Illuminance (24°) : 7072 lux @ 2 m
- Illuminance (37°) : 2964 lux @ 2 m
- Illuminance (24°) : 1132 lux @ 5 m
- Illuminance (37°) : 474 lux @ 5 m
- CRI : 96
- Optional Controllers : DMX
- Power and Current : 150 W, 1.3A @ 120 V, 60 Hz
- Power and Current : 150 W, 0.7 A @ 230 V, 50 Hz

INCLUS

- EVE E-160ZQ
- Power cord
- Gel frame
- Metal gobo holder
- Glass gobo holder
- QRG - Quick reference guide

