

Followspot 200ST

EN RÉSUMÉ

- Portable, LED followspot emits a tight beam with a crisp edge
- Backlit silicon buttons provide a tactile response in dark environments
- Relocated power and DMX connectors ensure smooth operation with no obstacles
- Mechanical iris reduces beam diameter to highlight specific subjects
- Built-in CTO filter lowers color temperature to match tungsten lamps
- Set up and tear down in seconds with the included tripod
- Built-in DMX allows remote control operation and syncing with the rest of the performance

CARACTÉRISTIQUES TECHNIQUES

- DMX Channels : 3
- DMX Connectors : 3-pin XLR
- Colors : 7 + open
- Light Source : 1 LED (cool white) 200 W, 15.8A, 50,000 hours life expectancy
- Lumens : 9,349
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Weight : 14.6 lb (6.6 kg)
- Size : 22.9 x 11 x 8.5 in (582 x 279 x 216 mm)
- Approvals : CE, UKCA, ROHS
- Color temperature : 13,000 K
- Color temperature (CTO) : 4,000 K
- Strobe Rate : 0 to 25 Hz
- Stand Height : 2.8 to 3.8 ft (0.8 to 1.2 m)
- Zoom Angle (manual) : 12° to 17°
- Iris (min) : 5° (at tightest zoom)
- Illuminance (12°) : 54,569 lux @ 2 m
- Illuminance (12°) : 8,731 lux @ 5 m
- Power and Current : 264 W, 2.2 A @ 120 V, 60 Hz
- Power and Current : 258 W, 1.2 A @ 230 V, 50 Hz
- Fits Tripod Sizes : 1.4 in (35 mm)
- Optional Controllers : DMX

INCLUS

- Followspot 200ST
- Power cord
- Tripod
- QRG

