

Intimidator Spot 360QD

Donnez une nouvelle dimension à vos prestations avec Intimidator Spot 360QD, la première lyre CHAUVET DJ avec technologie RGBL. Son moteur LED offre une palette chromatique étendue, un indice de rendu des couleurs amélioré et une optique de précision, pour un rendu plus fidèle et encore plus de possibilités créatives.

Les deux prismes rotatifs permettent de créer des effets couvrant une large zone, tandis que la mise au point motorisée garantit des gobos nets à différentes distances de projection. Le mode Totem concentre les effets sur la piste de danse, et le contrôle sans fil intégré simplifie l'installation en réduisant le nombre de câbles.

Son châssis léger en composite de fibre de carbone facilite le transport et la manipulation. Adapté aussi bien aux prestations mobiles qu'aux installations permanentes, Intimidator Spot 360QD trouve naturellement sa place aussi bien sur scène que dans les salles de réception, les clubs et les lieux de divertissement.



EN RÉSUMÉ

- Innovative moving head designed for the mobile entertainer or permanent installation
- Wide color range, increased CRI, and crystal-clear optics from the RGBL light engine
- Carbon fiber composite housing material is exceptionally strong, resists corrosion, and reduces weight
- Built-in D-Fi transceiver for wireless DMX or master/slave communications
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- Dual rotating prisms split the beam for great effects and cover a larger area
- Project crisp gobos from nearly any distance with the motorized focus
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- PowerCON®-compatible power input/output connections saves setup time
- Onboard USB-C port allows for quick software updates

CARACTÉRISTIQUES TECHNIQUES

- DMX Channels : 11 or 18
- DMX Connectors : 3- and 5-pin XLR
- Pan and Tilt : 540° / 270°
- Pan and Tilt Ranges : 540°, 360°, 180° pan/270°, 180°, 90° tilt
- Gobos : 7 + open (6 metal + 1 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds
- Light Source : 1 LED (quad-color RGBL) 220W, (2.5A), 50,000 hours life expectancy.
- Strobe Rate : 0 to 25 Hz
- Beam Angle : 17°
- Illuminance : 17,242 lux @ 2 m, 2,759 lux @ 5 m
- Power Linking : 4 units @ 120 V; 8 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 324 W, 2.7 A @ 120 V, 60 Hz
- Gobo Size : 24 mm outside, 20 mm image, 0.5 mm max thickness
- Weight : 20,4 lb (9,2 kg)
- Size : 12.5 x 8.6 x 17.1 in (319 x 220 x 435 mm)
- Approvals : CE, RoHS, MET
- Prism : 5-facet linear, bi-directional at variable speeds
- Prism : 6-facet round, bi-directional at variable speeds
- Optional Controllers : RFC, RFC-XL

INCLUS

- Intimidator Spot 360QD
- Power cord
- PowerCON to bare end (EU only)
- Hanging brackets
- Quick Reference Guide